

RE-VERBER-AIR HEATER SUBMITTAL SHEET

UH SERIES UNIT HEATERS

GAS-FIRED, INDUCED DRAFT, HOT AIR UNIT HEATERS & ACCESSORIES

PROJECT ID: _____	ADDRESS: _____
PROJECT NAME: _____	_____
DATE: _____	CITY: _____ STATE: _____ ZIP: _____
Submitted By: _____ Address: _____	
Company: _____	_____
Phone: _____	City: _____
Email: _____	State: _____ Zip: _____
.....	
Engineer: _____	Contractor: _____
Phone/Email: _____	Phone/Email: _____
Address: _____	Address: _____
City: _____	City: _____
State: _____ Zip: _____	State: _____ Zip: _____

QTY.	MODEL NO.	TAG	INDICATE GAS TYPE	BTU/h		APPROX. HEAT THROW	AVERAGE AIR TEMP. RISE	VENT LENGTH ¹		TYP. OR RCMD. MOUNTING HEIGHTS ¹	SHIP WEIGHT
				INPUT	OUTPUT			MIN.	MAX.		
	UH-30		Nat. or Prop.	30,000	24,000	26 ft.	45°F	3 ft.	30 ft.	8 to 12 ft.	77 lbs.
	UH-45		Nat. or Prop.	45,000	36,000	28 ft.	45°F	3 ft.	30 ft.	8 to 14 ft.	77 lbs.
	UH-60		Nat. or Prop.	60,000	48,000	37 ft.	45°F	3 ft.	30 ft.	10 to 16 ft.	98 lbs.
	UH-75		Nat. or Prop.	75,000	60,000	39 ft.	45°F	3 ft.	30 ft.	10 to 18 ft.	98 lbs.

¹ Deduct 3 ft. (on 3 in. vent) or 5 ft. (on 4 in. vent) for each elbow added to venting.



UH SERIES FEATURED SPECIFICATIONS

APPROVALS

- ETL Listed
- Commercial/Industrial Approval
- Residential Use
- Indoor Use Only

VOLTAGE

- 120 VAC/60 Hz (primary)
- 24 VAC (thermostatic)
- Single phase

MANIFOLD PRESSURE (Inches W.C.)

- Natural Gas: 3.5
- Propane: 10.0

INLET PRESSURE (Inches W.C.)

- Natural Gas: 5.0 to 14.0
- Propane: 11.0 to 14.0

GAS CONNECTION

- ½" NPT
- Field connect to valve

VENT & INLET CONNECTION

- Category I or III venting
- Rear, horizontal discharge/inlet
- 3" to 4" inlet adapter included

MOUNTING

- Four (4) suspension points
- Slotted mounting brackets accommodate joists on 16 or 24 inch centers
- 180° mounting

OTHER

- Finger-proof fan guards standard
- External indicator lights
- External thermostatic connection
- Approved for 0–2,000 ft. elevations without modifications
- Supplied standard as separated combustion

LIMITED WARRANTY

- 1 year—Components
- 5 years—Heat exchangers
- 10 years—Burners

MODEL	FLA AMPS	MOTOR TYPE	MOTOR HP	FAN DIAMETER	AXIAL FAN ROTATION	GAS CONNECTION	INLET & VENT CONNECTION
UH-30	2.7	SP	1/15	10 in.	CCW	1/2" NPT	3" O.D.
UH-45	2.7	SP	1/15	10 in.	CCW	1/2" NPT	3" O.D.
UH-60	4.0	PSC	1/12	14 in.	CCW	1/2" NPT	4" O.D.
UH-75	4.0	PSC	1/12	14 in.	CCW	1/2" NPT	4" O.D.

FIELD CONVERSION REFERENCE CHART

SUPPLIED AS	CONVERSION TO	AVAILABILITY	PART REFERENCE ²
Separated Combustion	Power Vented, Room Air	Standard	See IOPM
Natural Gas	Propane Gas	Optional	HKP
0–2,000 MSL	2,001–4,500 MSL	Optional	HKN or HKP
0–2,000 MSL	4,501–7,000 MSL	Optional	HKN or HKP
0–2,000 MSL	7,001–9,500 MSL	Optional	HKN or HKP

² Consult heater Installation, Operation, Parts, and Maintenance Manual for conversion kit reference and instructions.

OPTIONAL ACCESSORIES

- ☐ **CVK-3** 3" Concentric Vent Kit for use when venting and combustion air is desired through a single wall or roof penetration. For use with UH-30 and UH-45 models. No vent pipe or B-vent material is included.
- ☐ **CVK-4** 4" Concentric Vent Kit for use when venting and combustion air is desired through a single wall or roof penetration. For use with UH-60 and UH-75 models. No vent pipe or B-vent is included.
- ☐ _____
- ☐ _____
- ☐ _____



216 Avenida Fabricante
Suite 207
San Clemente, CA 92672

Phone: (760) 779-1640
www.gasoutdoorpatioheaters.com